GNU Calc Reference Card

(for GNU Emacs version 30)

Starting and Stopping

start/stop standard Calc	`C-x * c`
start/stop X keypad Calc	`C-x * k`
start/stop either:	`C-x * *`
stop standard Calc	`q`
Calc tutorial	`C-x * t`
run Calc in other window	`C-x * o`
quick calculation in minibuffer	`C-x * q`

Getting Help

The `h` prefix key is Calc's analogue of `C-h` in Emacs.

quick summary of keys	`?`
describe key briefly	`h c`
describe key fully	`h k`
describe function or command	`h f`
read Info manual	`h i` or `C-x * i`
read full Calc summary	`h s` or `C-x * s`

Error Recovery

abort command in progress	`C-g`
display recent error messages	`w`
undo last operation	`U`
redo last operation	`D`
recall last arguments	`M-RET`
edit top of stack	`` ` ``
reset Calc to initial state	`C-x * 0` (zero)

Transferring Data

grab region from a buffer	`C-x * g`
grab rectangle from a buffer	`C-x * r`
grab rectangle, summing columns	`C-x * :`
grab rectangle, summing rows	`C-x * _`
yank data to a buffer	`C-x * y`

Also, try `C-k`/`C-y` or X cut and paste.

Examples

In RPN, enter numbers first, separated by `RET` if necessary, then type the operator. To enter a calculation in algebraic form, press the apostrophe first.

	RPN style:	**algebraic style:**
Example:	`2 RET 3 +`	`' 2+3 RET`
Example:	`2 RET 3 + 4 *`	`' (2+3)*4 RET`
Example:	`2 RET 3 RET 4 + *`	`' 2*(3+4) RET`
Example:	`3 RET 6 + Q 3 ^`	`' sqrt(3+6)^3 RET`
Example:	`P 3 / n S`	`' sin(-pi/3) RET =`

© 2025 Free Software Foundation, Inc. Permissions on back.

Arithmetic

add, subtract, multiply, divide	`+`, `-`, `*`, `/`
raise to a power, nth root	`^`, `I ^`
change sign	`n`
reciprocal $1/x$	`&`
square root $\sqrt{x}$	`Q`
set precision	`p`
round off last two digits	`c 2`
convert to fraction, float	`c F`, `c f`
enter using algebraic notation	`' 2+3*4`
refer to previous result	`' 3*$^2`
refer to higher stack entries	`' $1*$2^2`
finish alg entry without evaluating	`LFD`
set mode where alg entry used by default	`m a`

Stack Commands

Here S_n is the nth stack entry, and N is the size of the stack.

key	*no prefix*	*prefix n*	*prefix −n*
`RET`	copy S_1	copy $S_{1..n}$	copy S_n
`LFD`	copy S_2	copy S_n	copy $S_{1..n}$
`DEL`	delete S_1	delete $S_{1..n}$	delete S_n
`M-DEL`	delete S_2	delete S_n	delete $S_{1..n}$
`TAB`	swap $S_1 \leftrightarrow S_2$	roll S_1 to S_n	roll S_n to S_N
`M-TAB`	roll S_3 to S_1	roll S_n to S_1	roll S_N to S_n

With a 0 prefix, these copy, delete, or reverse the entire stack.

Display

scroll horizontally, vertically	`< >`, `{ }`
home cursor	`o`
line numbers on/off	`d l`
trail display on/off	`t d`
scientific notation	`d s`
fixed-point notation	`d f`
floating-point (normal) notation	`d n`
group digits with commas	`d g`

For display mode commands, `H` prefix prevents screen redraw and `I` prefix temporarily redraws top of stack.

Notations

scientific notation	`6.02e23`
minus sign in numeric entry	`_23` or `23 n`
fractions	`3:4`
complex numbers	(x, y)
polar complex numbers	$(r; \theta)$
vectors (commas optional)	`[1, 2, 3]`
matrices (or nested vectors)	`[1, 2; 3, 4]`
error forms (`p` key)	`100 +/- 0.5`
interval forms	`[2 .. 5)`
modulo forms (`M` key)	`6 mod 24`
HMS forms	`5@ 30' 0"`
date forms	`<Jul 4, 1992>`
infinity, indeterminate	`inf`, `nan`

Scientific Functions

ln, $\log_{10}$, $\log_b$	`L`, `H L`, `B`
exponential e^x, 10^x	`E`, `H E`
sin, cos, tan	`S`, `C`, `T`
arcsin, arccos, arctan	`I S`, `I C`, `I T`
inverse, hyperbolic prefix keys	`I`, `H`
two-argument arctan	`f T`
degrees, radians modes	`m d`, `m r`
pi (π)	`P`
factorial, double factorial	`!`, `k d`
combinations, permutations	`k c`, `H k c`
prime factorization	`k f`
next prime, previous prime	`k n`, `I k n`
GCD, LCM	`k g`, `k l`
random number, shuffle	`k r`, `k h`
minimum, maximum	`f n`, `f x`
error functions erf, erfc	`f e`, `I f e`
gamma, beta functions	`f g`, `f b`
incomplete gamma, beta functions	`f G`, `f B`
Bessel J_ν, Y_ν functions	`f j`, `f y`
complex magnitude, arg, conjugate	`A`, `G`, `J`
real, imaginary parts	`f r`, `f i`
convert polar/rectangular	`c p`

Financial Functions

enter percentage	`M-%`
convert to percentage	`c %`
percentage change	`b %`
present value	`b P`
future value	`b F`
rate of return	`b T`
number of payments	`b #`
size of payments	`b M`
net present value, int. rate of return	`b N`, `b I`

Above computations assume payments at end of period. Use `I` prefix for beginning of period, or `H` for a lump sum investment.

straight-line depreciation	`b S`
sum-of-years'-digits	`b Y`
double declining balance	`b D`

Units

enter with units	`' 55 mi/hr`
convert to new units, base units	`u c`, `u b`
convert temperature units	`u t`
simplify units expression	`u s`
view units table	`u v`

Common units:

distance: `m`, `cm`, `mm`, `km`; `in`, `ft`, `mi`, `mfi`; `point`, `lyr`
volume: `l` or `L`, `ml`; `gal`, `qt`, `pt`, `cup`, `floz`, `tbsp`, `tsp`
mass: `g`, `mg`, `kg`, `t`; `lb`, `oz`, `ton`
time: `s` or `sec`, `ms`, `us`, `ns`, `min`, `hr`, `day`, `wk`
temperature: `degC`, `degF`, `K`

GNU Calc Reference Card

Programmer's Functions

binary, octal, hex display	`d 2`, `d 8`, `d 6`
decimal, other radix display	`d 0`, `d r`
display leading zeros	`d z`
entering non-decimal numbers	`16#7FFF`
binary word size	`b w`
binary AND, OR, XOR	`b a`, `b o`, `b x`
binary DIFF, NOT	`b d`, `b n`
left shift	`b l`
logical right shift	`b r`
arithmetic right shift	`b R`
integer quotient, remainder	`\`, `%`
integer square root, logarithm	`f Q`, `f I`
floor, ceiling, round to integer	`F`, `I F`, `R`

Variables

Variable names are single digits or whole words.

store to variable	`s t`
store and keep on stack	`s s`
recall from variable	`s r`
shorthands for digit variables	`t` *n*, `s` *n*, `r` *n*
unstore, exchange variable	`s u`, `s x`
edit variable	`s e`

Vector Operations

vector of 1, 2, ..., *n*	`v x` *n*
vector of *n* counts from *a* by *b*	`C-u v x`
vector of copies of a value	`v b`
concatenate into vector	`|`
pack many stack items into vector	`v p`
unpack vector or object	`v u`
length of vector (list)	`v l`
reverse vector	`v v`
sort, grade vector	`V S`, `V G`
histogram of vector data	`V H`
extract vector element	`v r`
matrix determinant, inverse	`V D`, `&`
matrix transpose, trace	`v t`, `V T`
cross, dot products	`V C`, `*`
identity matrix	`v i`
extract matrix row, column	`v r`, `v c`
intersection, union, diff of sets	`V ^`, `V V`, `V -`
cardinality of set	`V #`
add vectors elementwise (i.e., map `+`)	`V M +`
sum elements in vector (i.e., reduce `+`)	`V R +`
sum rows in matrix	`V R _ +`
sum columns in matrix	`V R : +`
sum elements, accumulate results	`V U +`

Algebra

enter an algebraic formula	`' 2x+3y^2`
enter an equation	`' 2x^2=18`
symbolic (vs. numeric) mode	`m s`
fractions (vs. float) mode	`m f`
suppress evaluation of formulas	`m O`
return to default evaluation rules	`m D`
"Big" display mode	`d B`
C, Pascal, FORTRAN modes	`d C`, `d P`, `d F`
TeX, LaTeX, eqn modes	`d T`, `d L`, `d E`
Maxima	`d X`
Unformatted mode	`d U`
Normal language mode	`d N`
simplify formula	`a s`
put formula into rational form	`a n`
evaluate variables in formula	`=`
evaluate numerically	`N`
let variable equal a value in formula	`s l` *x*=*val*
declare properties of variable	`s d`
Common decls: `pos`, `int`, `real`, `scalar`, [*a*..*b*].	
expand, collect terms	`a x`, `a c`
factor, partial fractions	`a f`, `a a`
polynomial quotient, remainder, GCD	`a \`, `a %`, `a g`
derivative, integral	`a d`, `a i`
taylor series	`a t`
principal solution to equation(s)	`a S`
list of solutions	`a P`
generic solution	`H a S`
apply function to both sides of eqn	`a M`
rewrite formula	`a r`

Example: `a r a*b + a*c := a*(b+c)`
Example: `a r sin(x)^2 := 1-cos(x)^2`
Example: `a r cos(n pi) := 1 :: integer(n) :: n%2 = 0`
Example: `a r [f(0) := 1, f(n) := n f(n-1) :: n > 0]`
Put rules in `EvalRules` to have them apply automatically.
Put rules in `AlgSimpRules` to apply during `a s` command.
Common markers: `opt`, `plain`, `quote`, `eval`, `let`, `remember`.

Numerical Computations

sum formula over a range	`a +`
product of formula over a range	`a *`
tabulate formula over a range	`a T`
integrate numerically over a range	`a I`
find zero of formula or equation	`a R`
find local min, max of formula	`a N`, `a X`
fit data to line or curve	`a F`
mean of data in vector or variable	`u M`
median of data	`H u M`
geometric mean of data	`u G`
sum, product of data	`u +`, `u *`
minimum, maximum of data	`u N`, `u X`
sample, pop. standard deviation	`u S`, `I u S`

Selections

select subformula under cursor	`j s`
select *n*th subformula	`j` *n*
select more	`j m`
unselect this, all formulas	`j u`, `j c`
copy indicated subformula	`j RET`
delete indicated subformula	`j DEL`
commute selected terms	`j C`
commute term leftward, rightward	`j L`, `j R`
distribute, merge selection	`j D`, `j M`
isolate selected term in equation	`j I`
negate, invert term in context	`j N`, `j &`
rewrite selected term	`j r`

Graphics

graph function or data	`g f`
graph 3D function or data	`g F`
replot current graph	`g p`
print current graph	`g P`
add curve to graph	`g a`
set number of data points	`g N`
set line, point styles	`g s`, `g S`
set log vs. linear *x, y* axis	`g l`, `g L`
set range for *x, y* axis	`g r`, `g R`
close graphics window	`g q`

Programming

begin, end recording a macro	`C-x (`, `C-x )`
replay keyboard macro	`X`
read region as written-out macro	`C-x * m`
if, else, endif	`Z [`, `Z :`, `Z ]`
equal to, less than, member of	`a =`, `a <`, `a {`
repeat *n* times, break from loop	`Z <`, `Z >`, `Z /`
"for" loop: start, end; body, step	`Z (`, `Z )`
save, restore mode settings	`Z ‘`, `Z ’`
query user during macro	`Z #`
put finished macro on a key	`Z K`
define function with formula	`Z F`
edit definition	`Z E`
record user-defined command permanently	`Z P`
record variable value permanently	`s p`
record mode settings permanently	`m m`

Copyright © 2025 Free Software Foundation, Inc.
designed by Dave Gillespie and Stephen Gildea,
for GNU Emacs Calc.

Released under the terms of the GNU General Public License version 3 or later.

For more Emacs documentation, and the TeX source for this card, see the Emacs distribution, or `https://www.gnu.org/software/emacs`